

US006726436B2

(12) United States Patent

Baumann et al.

(10) Patent No.: US 6,726,436 B2

(45) **Date of Patent:** Apr. 27, 2004

(54) MODULAR FRAME LOAD HANDLER WITH TRANSLATABLE BOOM CARRIAGE

(75) Inventors: James A. Baumann, Sheboygan, WI

(US); Travis A. Stuart, Ozaukee, WI (US); Daniel K. Schlegel, Milwaukee, WI (US); David G. Petrovic, Ozaukee, WI (US); Philip G. Schaffner, Ozaukee, WI (US); Richard F. King,

Ozaukee, WI (US); James R. Wisnoski, Dakota, MN (US)

(73) Assignee: **ULG OmniQuip, Inc.**, Port

Washington, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/852,669

(22) Filed: May 11, 2001

(65) Prior Publication Data

US 2001/0041123 A1 Nov. 15, 2001

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/568,798, filed on May 11, 2000.

(51) Int. Cl.⁷ E02F 3/00

(56) References Cited

U.S. PATENT DOCUMENTS

3,131,493 A 5/1964 LeTourneau 3,799,362 A 3/1974 Oswald et al.

3,895,728	A	7/1975	Heggen	
4,151,920	A	5/1979	Shoup	
4,215,971	A	8/1980	Itey-Bernard	
4,224,818	A	9/1980	Jones et al.	
4,290,642	A *	9/1981	Wise	296/182
4,415,181	A	11/1983	McCall et al.	
4,621,973	Α	11/1986	Langenfeld et al.	
4,874,285	A	10/1989	Bubik	

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 043 228	1/1982	
EP	0043228 A1 *	1/1982	B62D/29/00
EP	0867 566 A2	9/1998	

OTHER PUBLICATIONS

International Search Report dated Mar. 13, 2002 during prosecution of International Application No. PCT/US01/15261.

Primary Examiner—Eileen D. Lillis
Assistant Examiner—Michael Lowe
(74) Attorney, Agent, or Firm—Dickstein Shapiro Morin &
Oshinsky LLP

(57) ABSTRACT

A load handler with a modular frame and the manufacture and assembly of the frame and loader and components that may be used therein. A frame is provided that has a low pivot point for a boom. The frame has left and right side rails, and front and rear cross rails, each having a closed cross-section construction. The side rails and cross rails are modular and the cross rails of a selected size are configured to fit a plurality of sizes of side rails, such that the same size cross rails may be used to construct a variety sizes and capabilities of load handling vehicles in a flow type manufacturing process. A structural beam is provided having plates interconnected along their lengths to form the beam having a box-shaped closed cross-section having a perimeter generally along the widths of the plates and forming a beam cavity within the perimeter.

12 Claims, 15 Drawing Sheets

